

# SISTEMAS DVR



HR16/ 16CH



## ESPECIFICACIONES:

MODELO**	HR 16
COMPRESION	H.264
TIPO DE SEÑAL	NTSC / PAL
ENTRADA DE CAMARA	16 CANALES
ENTRADA DE AUDIO/ SALIDA	4CANALES / 1 CANAL
ENTRADA DE SENSORES	16 CANALES
ENTRADA DE ALARMA	4 CANALES
VELOCIDAD DE DISPLAY	480fps(NTSC), 400fps(PAL) at CIF resolution
VELOCIDAD DE GRABACION	120fps(NTSC), 100fps(PAL) at CIF resolution
RESOLUCION DEL VIDEO	D1, HalfD1, CIF
SALIDA DE MONITOR	Análogo RGB: 1VGA, composite : 1BNC
DIVISION DE PANTALLA	1/4/9/16 Pantalla dividida, auto secuencial
SALIDA DE SPOT	Composite : 1BNC
ALMACENAJE DE INFORMACION	SATA HDD, USB, CD-RW, manejo de red
CONTROL PTZ	RS485,RS232
CONTROLES	Mouse, Control Remoto, Botones en la Parte frontal
SISTEMA OPERATIVO	Embedded Linux
SOPORTES DE RED	TCP/IP

\*\* Estas especificaciones están sujetas a cambios sin previo aviso.



http: [WWW.MVPANAMA.NET](http://WWW.MVPANAMA.NET)  
 E-MAIL: info @mvpanama.net  
 Phone: (507) 393-8600 / 393-8601



**Triplex**  
(Live Display, Recording, Network)



**Multiple Screen division**(1, 4, 9, 16, PIP)



**H.264 Hardware compression**  
(High Quality video)



**Easy to Use and convenient GUI**



**Embedded Linux Operating System**



**Fast operation by mouse and remote controller**



**Simultaneous Monitoring via Composite, VGA**



**Network : DHCP & Static IP Supported**



**Backup and Firmware Update by USB drive**



**Event Recording : Motion detection and sensor**

