

SISTEMAS DVR













HR-09/9CH

ESPECIFICACIONES:

MODELO**	HR-09	
TIPO DE SEÑAL	NTSC	PAL
ENTRADA DE CAMARA	9 CHANNEL	
ENTRADA DE AUDIO / SALIDA	4CH Entrada / 1CH Salida	
ENTRADA DE SENSOR	9CH / 16CH	
ENTRADA DE ALARA	4CH	
VELOCIDAD DE DISPLAY	270fps (NTSC), 225fps(PAL) At CIF resolución	
VELOCIDAD DE GRABACION	120fps(NTSC), 100fps(PAL) CIF resolución	
RESOLUCION DE VIDEO	D1, Half D1, CIF	
SALIDA DE MONITOR	Analogo RGB : 1VGA, Composite : 1BNC	
SALIDA DE SPOT	Composite : 1BNC	
DIVISION DE PANTALLA	1/4/9/16 dividida y auto secuencial	
ALMACENAJE	SATA HDD, USB,CD-RW, por internet	
PTZ CONTROL	RS485,RS232	
MODO DE CONTROL	Mouse, Control Remoto, botones frontales.	
SISTEMA OPERATIVO	Embedded Linux	
SOPORTE DE RED	TCP/IP	

** Estas especificaciones están sujetas a cambios sin previo aviso.

-  Triplex
(Live Display, Recording, Network)
-  H,264 Hardware compression
(High Quality video)
-  Embedded Linux Operating System
-  Simultaneous Monitoring via
Composite, VGA
-  Backup and Firmware Update
by USB drive
-  Multiple Screen division(1, 4, 9, PIP)
-  Easy to Use and convinient GUI
-  Fast operation by mouse and
remote controller
-  Network : DHCP & Static IP Supported
-  Event Recording :
Motion detection and sensor

